ST/U10.3.1-825 1/5



PRODUCT-DETAILS

ST/U10.3.1-825

Touch panel, Wi-Fi, glass black / gold



General Information

ST/U10.3.1-825 2/5

Extended Product Type	ST/U10.3.1-825
Product ID	2TMA310051B0003
EAN	6955891819481
Catalog Description	Touch panel, Wi-Fi, glass black / gold

Freely programmable Touch panel featuring a 10-inch IPS screen with 1280*800 resolution that combines smart home automation and door communication in one device for residential applications, hotels, and commercial buildings. SmartTouch 10 offers home control and monitoring of the free@home, or KNX system and the fully integrated functions of ABB Welcome®.

Control, observe and manage your entire installation on one device: Switching -Dimming - Slider - Blind - RGBW control element - Step switch - Scene switch - Display element - Audio control element. With scene function, logic functions, presence simulation and time programs. SmartTouch® 10" can also be used as an end device for communication with the ABB-Welcome outdoor stations, and as part of the ABB-Welcome door communication system.

Functions

KNX:

- A total of 450 control elements are displayed on a maximum of 25 pages.

- 80 fault and alarm messages

- 30 logic functions - 40 timers

- presence simulation for 20 participants

- 10 scene actuators

- 3 object RTC

- Equipped with a hearing loop for coupling the audio signal into hearing aids - Page display with a maximum of 18 touch surfaces on one page

- Twisted pair connection provides a single page with a maximum of 18 controls. - Alternatively, for additional control, connection via wi-fi delivers the same amount of control and features as the free@home App.

Welcome:

- Integrated IP Gateway - Possibility to integrate ONVIF IP cameras

External power supply: 20-32 VDC (SELV) or via the ABB-Welcome system controller (Consumer units: 14).

Display size: 25,4cm (10"): Display resolution: 1280*800 : Display screen: IPS display Dimensions (L x W x D): (180.2mm x 254.6mm x 17.5mm) Flush or wall mounted, mount for desktop installation The flat design slim real metal frame sits almost flush with the wall (14mm) and is available in 4 colours (stainless steel, anthracite, gold and rose gold) and black or

Installation Instructions and 2CKA001473B5343 Manuals Instructions and 2CKA001373B5343 Manuals (Part 2) Mounting Type Flush Mounted Surface Mounted **Mounting Position** horizontal Mounting Height Optimum 1.5 m **Modular Components** Complete Device Included

Environmental	
Ambient Air	Operation 0 +45 °C
Temperature	

Long Description

ST/U10.3.1-825 3/5

Degree of Protection IP20

Technical	
Data Sheet, Technical Information	2CKA001373B5351
Communication Interface	Wi-Fi
Compatible Bus Systems	free@home (TP) KNX (TP)
Product Range	free@home KNX Welcome
Transmission Standard	2-Wire Twisted Pair Wiring Wireless LAN
Display Type	TFT Touch
Manual Operation	Yes
Terminal Type	Screw Terminals, Pluggable

Electrical	
Rated Voltage (U _r)	20 32 V
Auxiliary Voltage AC/DC	24 V DC
Rated Current (In)	0.5 A

Design	
Housing Material	Stainless steel
Material	Thermoplastic Glass
	Stainless steel
Color	glass black / gold

Dimensions	
Product Net Width	254.6 mm
Product Net Height	180.2 mm
Product Net Depth / Length	17.5 mm
Product Net Weight	953 g
Screen Size	10 in

Engineering	
Building Information	9AKK108470A2880
Modeling – BIM	

Ordering	
E-Number (Finland)	2818972
E-Number (Norway)	4544066
E-Number (Sweden)	1740190

ST/U10.3.1-825 4/5

E-Number (Switzerland) 305510385

ABB EcoSolutions

ABB EcoSolutions Yes

Circular Value	
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 38.8 %
Sustainable Material Content in Packaging (wt. %)	Recycled Cardboard - 93 %
Extended Product Lifetime	Product Upgradability
Offered with Takeback Services	Take Back for Recycling
Environmental Product	9AKK108469A0173

Material Compliance

Declaration - EPD

RoHS Declaration	2CKA200000E7720
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	2. Screens, Monitors, and Equipment Containing Screens Having a Surface Greater Than 100 cm²
WEEE B2C / B2B	Business To Consumer

Certificates and Declarations

Cyber Security Software Support Period	2 year
Declaration of Conformity - CE	2CKA100000E4597
EU Data Act Applicability and Compliance	2025 Applicable - Compliant
EU Data Act Compliance Declaration	9AKK108471A4300

External Classifications and Standards

ETIM 9	EC000783 - Signalling and operation panel for bus system
ETIM 10	EC000783 - Signalling and operation panel for bus system
eClass	V11.0 : 27143101
UNSPSC	39121801

Accessories

ST/U10.3.1-825 5/5

Identifier	Description	Type Quantity		Unit Of Measure
2TMA310161B0001	SmartTouch 10 SM Frame B	ST/A10.1-825	1	piece
2CKA006136A0212	Mounting box FM	6136/07 UP- 500	1	piece
2CDG120037R0011	CP-D24/2.5 Power Supply, 24 V DC, 2.5 A, MDRC	CP-D24/2.5	1	piece

Categories

Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow Door Entry & Access Control Systems \rightarrow Welcome \rightarrow Indoor Stations

Low Voltage Products and Systems → Building and Home Automation Solutions → free@home → Touch Panels → Touch Panels

Low Voltage Products and Systems → Building and Home Automation Solutions → free@home → User Operation → Thermostats

Low Voltage Products and Systems → Building and Home Automation Solutions → free@home → User Operation → Touch Panels

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow User\ Operation \rightarrow Control\ Elements \rightarrow Touch\ Panels$

Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow User Operation \rightarrow Thermostats Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow Visualisation, Display and Signalling \rightarrow Touch Panels







